

DATASHEET

DT-Mobil Easy COMBI 440/50 I, 12V, lid 40 l/min, nozzle

Order number: 10992

DESCRIPTION

DT-Mobile Easy 440/50 L COMBI, pump 12 V, 40

L/min, automatic nozzle, hinged lid



Product front view open



Product open, diagonally from the right



Product closed, diagonally from the right



Product detail view



Product detail view

TECHNICAL DATA

Medium	Diesel, AdBlue, Biodiesel, HVO, Heating Oil
Content Volume	440 l
Content volume secondary medium	50 l
Dimensions	80 x 78 x 118 cm
Weight	60 kg
Package Weight	58.5 kg
Use	mobile
Installation Location	transport
Material	LLPDE
Coating	uncoated
Container Colour	grey
Operating Voltage	12V DC 12V DC
Pump Drive	pump
Flow Rate	40 L/min (max.)
Dispensing Hose Length	4.80 m
Hose Diameter	dn 19
Stackable	Yes

Warranty in years	2.00
Assembly condition	mounted
Plug	Polzangen

EQUIPMENT

Lid Colour	orange
Lid	Yes
Hose Reel	no
Flow Meter Main Medium	without
Filter with Water Separator	no
Overfill Sensor	no
Bund Leak Indicator	no
Tank Data Management	no
Tanker Coupling	no
Heating	no
Forklift Pockets	Yes
Crane Eyes	no

SUITABLE MEDIA

Diesel
AdBlue
Biodiesel
HVO
Heating Oil

LOGISTICS

Package dimensions	100 x 80 x 120 cm
Units per box	1.00
Units per pallet	2
Pallet Dimensions	80 x 182 x 120 cm
Pallet weight	137 kg

ACCESSORIES



11111 - Digital flow meter K24 (210L,440L,Combi) for DT-Mobile Easy 210, 440,Combi 440/50



11059 - Contents gauge for DT-Mobile Easy COMBI



10229 - Plug DIN 9680, 3-pin, 6-24 V, max. 25A, IP54



10230 - Socket DIN 9680, 3-pin, 6-24V, max.25A, IP54



for safe storage



[Link to product](#)